

## 10-Port USB Charging Station with Adjustable Storage, 12V 8A (96W) USB Charger Output, Schuko Power Cord

### MODEL NUMBER: U280-010-ST-CEE





10-port USB charger keeps electronic devices, including tablets, smartphones and laptops, at full capacity via USB connection. Neatly organizes the devices within its adjustable storage brackets while charging.

#### Description

Whether you're at home or in the office, Tripp Lite's U280-010-ST-CEE 10-Port USB Charging Station provides plenty of ports and power to keep all your devices at 100% capacity. No more peering behind furniture to find an available outlet or unplugging one device to charge another. You can charge up to ten tablets, smartphones, laptops and other devices at the same time. This docking station for multiple devices doesn't require a computer, so you can take it anywhere AC power is available. To charge your USB devices, simply plug the included external dual-voltage (100V–240V) power supply into a Schuko outlet, and connect your devices to the available USB ports. The charger protects against overheating, overcurrent and overcharging—in fact, it stops charging as soon as your devices' batteries are at full capacity. A front LED indicates the unit is turned on and receiving AC power. The 10-port USB charger supports USB Battery Charging (BC) specification v1.2 and delivers up to 5V 2.4A to each port, which is plenty for charging even battery-intensive devices. Adjustable brackets on top of the charger act as storage, providing space to neatly organize devices while they charge. You can adjust the brackets to accommodate the number and size of the devices being charged.

#### Features

**Charges Up to 10 Devices at the Same Time**Ideal for charging tablets, smartphones, laptops and other devices at home or workConnect devices to unit's USB ports for proficient chargingCharges anywhere AC power is available—no computer required

**Provides Plenty of Juice for Charging**Delivers up to 5V 2.4A per port to charge battery-intensive devicesComplies with USB Battery Charging (BC) specification v1.2Protects against overheating, overcurrent and overcharging

Also Functions as Efficient StorageIncludes 14 adjustable brackets that neatly organize devices while they chargeBrackets are adjustable to accommodate number and size of devices being charged

Easy to UseIncluded external dual-voltage (100–240V) power supply plugs into a Schuko outletFront LED indicates when unit is turned on and receiving AC power

#### Highlights

- Up to 5V 2.4A per port for charging battery-intensive devices
- All ten ports support USB Battery Charging (BC) specification v1.2
- External dual-voltage power supply with Schuko plug
- Protects against overheating, overcurrent and overcharging
- Includes 14 adjustable storage brackets for organizing devices
- Charges anywhere AC power is available—no computer required (for 120V applications please use Tripp Lite's P013-Series cables, not included)

#### **Package Includes**

- U280-010-ST-CEE 10-Port USB Charging Station
- External Power Supply (Input: 100–240V, 50/60 Hz, 2A; Max Output: 12V 8A)
- C5 to CEE 7/7 Schuko Power Cord 3-ft.
- (14) Storage brackets
- Owner's manual



# **Specifications**

| OVERVIEW  |  |  |
|---|--|--|
| UPC Code  | 037332205698   |  |
| Product Type                                      | Charging Station                                       |  |
| Charging Form Factor                              | Charging Hub   |  |
| Device Compatibility                              | Phone; Tablet; Amazon Kindle                           |  |
| INPUT   |  |  |
| Nominal Input Voltage(s) Supported                | 120V AC; 230V AC                                       |  |
| Input Connection Type                             | USB-A Female   |  |
| Plug Type   | C5 to CEE 7/7 Schuko                                   |  |
| Voltage Compatibility (VAC)                       | 100; 110; 120; 125; 127; 200; 208; 220; 230; 240       |  |
| Input Plug Type                                   | CEE 7/7 Schuko   |  |
| OUTPUT  |  |  |
| Output Capacity                                   | 12V 8A   |  |
| Overload Protection                               | Yes  |  |
| POWER   |  |  |
| AC Adapter  | Input: 100-240V, 50/60Hz, 3.0A; Output: 12V, 8A, 3-ft. |  |
| External Power Supply Input Specs<br>(V / Hz / A) | 100-240V / 50/60Hz / 3.0A                              |  |
| External Power Supply Output<br>Specs (V / A)     | 12V / 8A   |  |
| External Power Supply Cord Length (m.)            | 1  |  |
| DC Barrel Plug                                    | OD: 5.5 x 2.5 x 10mm, Positive Pin, Negative Sleeve    |  |
| Power Consumption (Watts)                         | 34   |  |
| External Power Supply Plug(s)                     | CEE 7/7 Schuko   |  |
| Power Consumption Detail                          | 34W (Operating) 0.27W (Standby)                        |  |
| USER INTERFACE, ALERTS & CONTROLS                 |  |  |
| LED Indicators                                    | Power (Blue)   |  |
| CHARGING  |  |  |
| Number of Charging Ports                          | 10   |  |
| Total Charging Amps                               | 8A   |  |
| Total Charging Watts                              | 96   |  |



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

| Charging Port Type         USB           Charging Port Type         (10) USB A (FEMALE)           Charging Port Spetalis         USB-A : 2X/8A           Charging Method Detail         5V - 1.5A (7W)           PHYSICAL           Color         Black           Material of Construction         Polycarbonate           Unit Dimensions (hwd / in.)         1.000 x 9.400 x 4.700           Unit Dimensions (hwd / in.)         2.5 x 23.8 x 11.8           Unit Dimensions (hwd / in.)         0.666           Unit Weight (bs.)         0.666           Unit Weight (bs.)         0.666           Unit Weight (bs.)         0.666           Unit Weight (bs.)         0.667           Unit Weight (bs.)         0.666           Unit Weight (bs.)         0.667           Storage Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperatur                               |                                      |                                      |  |
|--|--------------------------------------|--------------------------------------|--|
| Charging Ports Details         USB-A: 12/VBA           Charging Ports / Amps         (10) 2.4A           Charging Method Detail         5V - 1.5A (7W)           PHYSICAL           Color         Black           Material of Construction         Polycarbonate           Unit Dimensions (twd / In)         1.000 x 9.400 x 4.700           Unit Dimensions (twd / In)         2.5 x 23.8 x 11.8           Unit Ponkaging Type         Box           Unit Weight (bs.)         0.66           Unit Weight (bs.)         0.66           Unit Weight (bs.)         0.66           Storage Temperature Range         4 to 12 F (-20 to 50 C)           Relative Humidity         20% to 80% RH. Non-Condensing           Connector 1         C10 (19 SA (MALE)           Side A - Connector 1         C10 (19 SA (MALE)           Side A - Connector 1         C10 (19 SA (MALE)           Side A - Connector 1         C10 (19 SA (MALE)           Driver Raquied         No           Quick Charge Complant         No           Quick Charge Complant         No           Quick Charge Complant         No           Side A - Connector 1         C10 (19 SA (MALE)           Driver Raquied         No           Quick C                               | Charging Method                      | USB                                  |  |
| Charging Ports / Amps         (10) 2.4A           Charging Method Detail         5V - 1.5A (7W)           PHYSICAL         Extended Construction           Octor         Black           Material of Construction         Polycarbonate           Unit Dimensions (twd / in.)         1.000 x 9.400 x 4.700           Unit Dimensions (twd / cm)         2.5 x 23.8 x 11.8           Unit Dimensions (twd / cm)         2.5 x 23.8 x 11.8           Unit Weight (bs.)         0.66           Unit Weight (bs.)         0.68           Unit Weight (bs.)         0.68           Unit Weight (bs.)         0.46           Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         4 to 122 F (-20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONECTIONS         100           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side A - Connector 1         10 USB (MALE)           PeratureEs & SPECIFICATIONS         Connector 1           Driver Required         No           Overcotage Conpliant         No           Overcotage Protection         Yes           Overcotage Protection | Charging Port Type                   | (10) USB A (FEMALE)                  |  |
| Charging Method Detail     5V - 1.5A (7W)       PHYSICAL       Color     Black       Material of Construction     Polycarborate       Unit Dimensions (twod / m)     1.000 x 9.400 x 4.700       Unit Dimensions (twod / m)     2.5 x 23.8 x 11.8       Unit Dimensions (twod / m)     2.5 x 23.8 x 11.8       Unit Weight (bs.)     0.66       Unit Weight (bs.)     0.66       Unit Weight (bs.)     0.30       ENVIRONMENTAL       Operating Temperature Range     41 to 95 F (5 to 35 C)       Storago Temperature Range     41 to 95 F (5 to 35 C)       Storago Temperature Range     41 to 95 F (5 to 35 C)       Storago Temperature Range     41 to 92 F (20 to 50 C)       Relative Humidity     20% to 80% RH, Non-Condensing       CONNECTIONS       Number of Ports     10       Side A - Connector 1     CEE 7/7 SCHUKO PLUG       Side B - Connector 1     (10) USB A (MALE)       Percures a specifications       Driver Required     No       Quick Charge Compliant     No       Quick Charge Compliant     No       Overcurent Protection     Yes       Quick Charge Compliant     No       Overcurent Protection     Yes       Quick Charge Compliant     No       Overcu  | Charging Ports Details               | USB-A: 12V/8A                        |  |
| PHYSICAL         Elack           Color         Black           Material of Construction         Polycarbonate           Unit Dimensions (hwd / m.)         1.000 x 9.400 x 4.700           Unit Dimensions (hwd / m.)         2.5 x 23.8 x 11.8           Unit Packaging Type         Box           Unit Weight (bs.)         0.66           Unit Weight (kg)         0.30           ENVIRONMENTAL         Operating Temperature Range           41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 25 F (20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side B - Connector 1         (10) USB A (MALE)           PEATURES & SPECIFICATIONS         Driver Required           Driver Required         No           Quick Charge Compliant         No           Overcurrent Protection         Yes           Overcurent Protection         Yes           Overcurent Protection         Yes           GaN Technology         No           IP20 Ra                   | Charging Ports / Amps                | (10) 2.4A                            |  |
| Color         Black           Material of Construction         Polycarbonate           Unit Dimensions (hwd / in.)         1.000 x 9.400 x 4.700           Unit Dimensions (hwd / orn)         2,5 x 23,8 x 11,8           Unit Packaging Type         Box           Unit Veight (bs.)         0.66           Unit Weight (bs.)         0.66           Unit Weight (bs.)         0.30           ENVIRONMENTAL         Operating Temperature Range           Querating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         4 to 122 F (-20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS         10           Number of Ports         10           Side A - Connector 1         CE 777 SCHUKO PLUG           Side B - Connector 1         10) USB A (MALE)           Priver Required         No           Quick Charge Compliant         No           Overvoltage Protection         Yes                                       | Charging Method Detail               | 5V - 1.5A (7W)                       |  |
| Material of Construction         Polycarbonate           Unit Dimensions (twd / cm)         1.000 x 9.400 x 4.700           Unit Dimensions (twd / cm)         2.5 x 23,8 x 11,8           Unit Packaging Type         Box           Unit Weight (lbs.)         0.66           Unit Weight (lbs.)         0.66           Unit Weight (lbs.)         0.30           ENVIRONMENTAL           Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 22 F (20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS           Number of Ports         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side A - Connector 1         CI0 USB A (MALE)           Priver Required         No           Quick Charge Compliant         No           Quick Charge Compliant         No           Overvoltage Protection         Yes           Overvoltage Protection         Yes           Overvoltage Protection         Yes           Overvoltage Protection         No           Bord         No           Divervoltage Protection   | PHYSICAL                             |                                      |  |
| Unit Dimensions (hwd / in.)         1.000 x 9.400 x 4.700           Unit Dimensions (hwd / cm)         2.5 x 23,8 x 11,8           Unit Packaging Type         Box           Unit Weight (bs.)         0.66           Unit Weight (kg)         0.30           ENVIRONMENTAL           Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 95 F (5 to 35 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS           Number of Ports         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side B - Connector 1         (10) USB A (MALE)           PEATURES & SPECIFICATIONS           Priver Required           No         Quick Charge Compliant           No         Quick Charge Compliant           No         Quick Charge Compliant           No         Quick Charge Compliant           Yes         Gal Technology           Quick Targe S & COMPLIANCE         Yes           Stanbards & COMPLIANCE         Yes   | Color                                | Black                                |  |
| Unit Dimensions (hwd / cm)         2,5 x 23,8 x 11,8           Unit Packaging Type         Box           Unit Weight (ks.)         0.66           Unit Weight (kg)         0.30           ENVIRONMENTAL           Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         41 to 95 F (5 to 35 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS           Number of Ports         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side B - Connector 1         (10) USB A (MALE)           PEATURES & SPECIFICATIONS           Priver Required         No           Quick Charge Compliant         No           Quick Charge Compliant         No           Overouting Protection         Yes           Quick Charge Compliant         No  | Material of Construction             | Polycarbonate                        |  |
| Unit Packaging Type         Box           Unit Weight (bs.)         0.66           Unit Weight (kg)         0.30           ENVIRONMENTAL            Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         -4 to 122 F (-20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS         10           Number of Ports         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side B - Connector 1         (10) USB A (MALE)           PertureS & SPECIFICATIONS         10           Driver Required         No           Quick Charge Compliant         No           Overcurrent Protection         Yes           Qvervoltage Protection         Yes           GaN Technology         No           IP20 Rated         No   | Unit Dimensions (hwd / in.)          | 1.000 x 9.400 x 4.700                |  |
| Unit Weight (bs.)       0.66         Unit Weight (kg)       0.30         ENVIRONMENTAL          Operating Temperature Range       41 to 95 F (5 to 35 C)         Storage Temperature Range       -4 to 122 F (-20 to 50 C)         Relative Humidity       20% to 80% RH, Non-Condensing         CONNECTIONS          Number of Ports       10         Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         PetATURES & SPECIFICATIONS          Driver Required       No         Quick Charge Compliant       No         Qvervoltage Protection       Yes         Qvervoltage Protection       Yes         GaN Technology       No         IP20 Rated       No  | Unit Dimensions (hwd / cm)           | 2,5 x 23,8 x 11,8                    |  |
| Unit Weight (kg)       0.30         ENVIRONMENTAL         Operating Temperature Range       41 to 95 F (5 to 35 C)         Storage Temperature Range       4 to 122 F (-20 to 50 C)         Relative Humidity       20% to 80% RH, Non-Condensing         CONNECTIONS       0         Number of Ports       10         Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         PEATURES & SPECIFICATIONS       10         Driver Required       No         Quick Charge Compliant       No         Qvercourrent Protection       Yes         Overvoltage Protection       Yes         Querourget No       No         Querourget No       No         GaN Technology       No         IP20 Rated       No  | Unit Packaging Type                  | Box                                  |  |
| ENVIRONMENTAL           Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         -4 to 122 F (-20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS         10           Number of Ports         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side B - Connector 1         (10) USB A (MALE)           Peatures & SPECIFICATIONS         10           Driver Required         No           Quick Charge Compliant         No           IP68 Rated         No           Overvoltage Protection         Yes           Quervoltage Protection         Yes           GaN Technology         No           IP20 Rated         No   | Unit Weight (Ibs.)                   | 0.66                                 |  |
| Operating Temperature Range         41 to 95 F (5 to 35 C)           Storage Temperature Range         -4 to 122 F (-20 to 50 C)           Relative Humidity         20% to 80% RH, Non-Condensing           CONNECTIONS           Number of Ports         10           Side A - Connector 1         CEE 7/7 SCHUKO PLUG           Side B - Connector 1         (10) USB A (MALE)           FEATURES & SPECIFICATIONS           Driver Required         No           Quick Charge Compliant         No           Qverrourten Protection         Yes           Qverrourten Protection         Yes           Quertodated         No           State A - Connector         No   | Unit Weight (kg)                     | 0.30                                 |  |
| Storage Temperature Range       -4 to 122 F (-20 to 50 C)         Relative Humidity       20% to 80% RH, Non-Condensing         CONNECTIONS         Number of Ports       10         Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         FEATURES & SPECIFICATIONS         Driver Required       No         Quick Charge Compliant       No         Overcurrent Protection       Yes         Overcurge Protection       Yes         GaN Technology       No         IP20 Rated       No  | ENVIRONMENTAL                        |                                      |  |
| Relative Humidity       20% to 80% RH, Non-Condensing         CONNECTIONS         Number of Ports       10         Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         FEATURES & SPECIFICATIONS         Driver Required       No         Quick Charge Compliant       No         Quick Charge Compliant       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No  | Operating Temperature Range          | 41 to 95 F (5 to 35 C)               |  |
| CONNECTIONS         Number of Ports       10         Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         FEATURES & SPECIFICATIONS         Priver Required         No         Quick Charge Compliant       No         Quick Charge Compliant       No         Overcurrent Protection       Yes         Overcurrent Protection       Yes         GaN Technology       No         IP20 Rated       No  | Storage Temperature Range            | -4 to 122 F (-20 to 50 C)            |  |
| Number of Ports       10         Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         FEATURES & SPECIFICATIONS         Priver Required         No         Quick Charge Compliant       No         IP68 Rated       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No  | Relative Humidity                    | 20% to 80% RH, Non-Condensing        |  |
| Side A - Connector 1       CEE 7/7 SCHUKO PLUG         Side B - Connector 1       (10) USB A (MALE)         FEATURES & SPECIFICATIONS         Driver Required       No         Quick Charge Compliant       No         IP68 Rated       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No   | CONNECTIONS                          |                                      |  |
| Side B - Connector 1       (10) USB A (MALE)         FEATURES & SPECIFICATIONS         Driver Required       No         Quick Charge Compliant       No         IP68 Rated       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No  | Number of Ports                      | 10                                   |  |
| FEATURES & SPECIFICATIONS         Driver Required       No         Quick Charge Compliant       No         IP68 Rated       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No   | Side A - Connector 1                 | CEE 7/7 SCHUKO PLUG                  |  |
| Driver Required       No         Quick Charge Compliant       No         IP68 Rated       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No   | Side B - Connector 1                 | (10) USB A (MALE)                    |  |
| Quick Charge Compliant       No         IP68 Rated       No         Overcurrent Protection       Yes         Overvoltage Protection       Yes         GaN Technology       No         IP20 Rated       No  | FEATURES & SPECIFICATIONS            |                                      |  |
| IP68 Rated     No       Overcurrent Protection     Yes       Overvoltage Protection     Yes       GaN Technology     No       IP20 Rated     No  | Driver Required                      | No                                   |  |
| Overcurrent Protection     Yes       Overvoltage Protection     Yes       GaN Technology     No       IP20 Rated     No  | Quick Charge Compliant               | No                                   |  |
| Overvoltage Protection     Yes       GaN Technology     No       IP20 Rated     No   | IP68 Rated                           | No                                   |  |
| GaN Technology     No       IP20 Rated     No  | Overcurrent Protection               | Yes                                  |  |
| IP20 Rated No STANDARDS & COMPLIANCE   | Overvoltage Protection               | Yes                                  |  |
| STANDARDS & COMPLIANCE   | GaN Technology                       | No                                   |  |
|  | IP20 Rated                           | No                                   |  |
| External Power Supply Certifications CE; FCC; UL; TUV; CCC; PSE; GS; RoHS  | STANDARDS & COMPLIANCE               |                                      |  |
|  | External Power Supply Certifications | CE; FCC; UL; TUV; CCC; PSE; GS; RoHS |  |
| Product Compliance RoHS; CE (Europe); REACH; FCC (USA)   | Product Compliance                   | RoHS; CE (Europe); REACH; FCC (USA)  |  |



| WARRANTY                               |                         |
|--|-------------------------|
| Product Warranty Period<br>(Worldwide) | 2-year limited warranty |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies